

## WEWA-TV<sup>®</sup> 17" (43,18 cm) PCAP Rear Mount Open-Frame Touchscreen Monitor

### GET IN TOUCH



Getting product information online  
[www.wewa.de](http://www.wewa.de)



Inquiries regarding orders, prices and availability  
T +49 (0) 234 890 3874-0  
F +49 (0) 234 890 3874-9



eMail  
[vertrieb@wewa.de](mailto:vertrieb@wewa.de)



### Resistant, scratchproof and vandalism-proof

The WEWA-TV 17" PCAP (Projective Capacitive Touchscreen-Technologie) Rear-Mount Open-Frame Touchscreen-Monitor convinces beside all the technical refinements with its compact design.

The PCAP Touch-Monitor owns an impact-resistant and robust high-quality touchscreen surface for the usage in harsh environments which is made of tempered glass.

The simplicity of the Touch-input is a comfortable alternative to the usage to mouse and keyboard.

Outstanding features of the WEWA-TV 17" PCAP Rear Mount Open-Frame Touchscreen Monitor

► PCAP (Projective Capacitive Touchscreen-Technologie), 10-point Touch (Win7/Win8/Win10)



## Specifications WEWA-TV 17" (43,18 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor

▶ Article name	WEWA-TV 17" (43,18 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor
▶ Artikelbestellnummer / EAN	WT0170TMRMOFSAW8 / 4260170311511
▶ Manufacturer	WEWA AG
▶ Screen size (Inch) / (cm)	17 / 43,18
▶ Certification	CE, FCC, CCC
▶ Aspect ratio	4:3
▶ Touch Technology	SAW (Surface Acoustic Wave) Touch
▶ Dimension (L x B x H)	391.5 x 323.5 x 48.4
▶ Active display area (mm)	337.9 (H) x 270.3 (V)
▶ Color depth	16.7 M
▶ Resolution	1280 x 1024@60Hz
▶ Pixel pitch (mm)	0.264 (H) x 0.264 (V)
▶ Response time (Typ)	5 ms
▶ Brightness (cd/m²)	250
▶ Backlight	LED
▶ Contrast ratio	1000:1
▶ Viewing angle horizontal   vertical (°)	170°   160°
▶ Input interface	VGA
▶ Touchscreen interface	USB
▶ Touch Point	Soft dual-points
▶ Touch activation Force	80g
▶ Surface Durability	Mohs' 7H
▶ Input Method	A finger or touch pen
▶ Touch response time	11ms
▶ Light transmission	92% (Glass thickness: 3mm)
▶ Minimum Touch Body	Ø2.5mm
▶ Expected life performance	More than 50 million touches
▶ Touch resolution (H x D)	4096 x 4096
▶ OS	WinXP, Win7, Win8, Linux compatible
▶ Power supply	DC: 12V ±5% (Adapter input: AC 100V-240V)
▶ Power consumption (W) / Stand-By Consumption (W)	<18 / <1
▶ OSD	Contrast, Brightness, Horizontal vertical image size and position, Warm, Cool, User custom color temperature, the language selection, Recall function, Exit OSD
▶ Operating temperature (°C)	0~45
▶ Storage temperature (°C)	-20~65
▶ Optional	Brackets, RS232 connecting cable
<b>I/O interface</b>	
▶ USB (Touchscreen to PC)	1x
▶ RS232 (Touchscreen to PC)	1x
▶ VGA (D-SUB 15 Pin)	1x
<b>Mounting options</b>	
▶ VESA-100-drilling, VESA-75-drilling	•
▶ Brackets (Optional)	•

### ▶ Accessories

- |  |  |
|--|--|
| <input type="radio"/> WEWA-TV 17" (43,18 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor | <input type="radio"/> 1x VGA cable                     |
| <input type="radio"/> 1x 12V DC Power supply unit  | <input type="radio"/> 1x Driver-CD (WinXP, Win7, Win8) |
|  | <input type="radio"/> 1x USB A-B cable                 |