

## WEWA-TV<sup>®</sup> 19" (48,26 cm) SAW Rear Mount Open-Frame Touchscreen Monitor

### GET IN TOUCH



Getting product information online  
[www.wewa.de](http://www.wewa.de)



Inquiries regarding orders, prices and availability  
 T +49 (0) 234 890 3874-0  
 F +49 (0) 234 890 3874-9



eMail  
[vertrieb@wewa.de](mailto:vertrieb@wewa.de)



### Resistant, scratchproof and vandalism-proof

The WEWA-TV 19" SAW (Surface Acoustic WAVE) Rear-Mount Open-Frame Touchscreen-Monitor convinces beside all the technical refinements with its compact design.

The SAW Touch-Monitor owns an impact-resistant and robust high-quality touchscreen surface for the usage in harsh environments which is made of tempered glass.

The simplicity of the Touch-input is a comfortable alternative to the usage to mouse and keyboard.

### Outstanding features of the WEWA-TV 19" SAW Rear Mount Open-Frame Touchscreen Monitor

▶ SAW (Surface Acoustic WAVE), 2 Finger Touch (Win7/Win8)



## Specifications WEWA-TV 19" (48,26 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor

▶ Article name	WEWA-TV 19" (48,26 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor
▶ Artikelbestellnummer / EAN	WT0190TMRMOFSAW8 / 4260170311528
▶ Manufacturer	WEWA AG
▶ Screen size (Inch) / (cm)	19 / 48,26
▶ Certification	CE, FCC, CCC
▶ Aspect ratio	4:3
▶ Touch Technology	SAW (Surface Acoustic Wave) Touch
▶ Dimension (L x B x H)	438.7 x 363.7 x 46.4
▶ Active display area (mm)	376.3 (H) x 301.1 (V)
▶ Color depth	16.7 M
▶ Resolution	1280 x 1024@60Hz
▶ Pixel pitch (mm)	0.294 (H) x 0.294 (V)
▶ Response time (Typ)	5 ms
▶ Brightness (cd/m <sup>2</sup> )	250
▶ Backlight	LED
▶ Contrast ratio	1000:1
▶ Viewing angle horizontal   vertical (°)	170°   160°
▶ Input interface	VGA
▶ Touchscreen interface	USB
▶ Touch Point	Soft dual-points
▶ Touch activation force	80g
▶ Surface Durability	Mohs' 7H
▶ Input method	A finger or touch pen
▶ Touch response time	11ms
▶ Light transmission	92% (Glass thickness: 3mm)
▶ Minimum Touch Body	Ø2.5mm
▶ Expected Life Performance	More than 50 million touches
▶ Touch resolution (H x D)	4096 x 4096
▶ OS	WinXP, Win7, Win8, Linux compatible
▶ Power supply	DC: +12V ±5% (input adaptor: AC 100V-240V)
▶ Power consumption (W) / Stand-By Consumption (W)	<18 / 1
▶ OSD	Contrast, Brightness, Horizontal vertical image size and position, Warm, Cool, User custom color temperature, the language selection, Recall function, Exit OSD
▶ Operating temperature (°C)	0~45
▶ Storage temperature (°C)	-20~65
▶ Optional	Brackets, RS232 connecting cable
<b>I/O interface</b>	
▶ USB (Touchscreen to PC)	1x
▶ RS232 (Touchscreen to PC)	1x
▶ VGA (D-SUB 15 Pin)	1x
<b>Mounting options</b>	
▶ VESA-100-drilling, VESA-75-drilling	•
▶ Brackets (Optional)	•

### ▶ Accessories

- |  |  |
|--|--|
| <input type="radio"/> WEWA-TV 19" (48,26 cm) SAW Rear-Mount Open-Frame Touchscreen Monitor | <input type="radio"/> 1x VGA cable                     |
| <input type="radio"/> 1x 12V DC Power supply unit  | <input type="radio"/> 1x Driver-CD (WinXP, Win7, Win8) |
|  | <input type="radio"/> 1x USB A-B cable                 |