

WEWA-TV[®] 21.5" (54,61 cm) PCAP Touchscreen Monitor

GET IN TOUCH



Getting product information online
www.wewa.de



Inquiries regarding orders, prices and availability
T +49 (0) 234 890 3874-0
F +49 (0) 234 890 3874-9



eMail
vertrieb@wewa.de



Resistant to scratches, water and dust

The WEWA-TV 21.5" PCAP (Projective Capacitive Touch) Touchscreen-Monitor convinces beside all the technical refinements with its compact design. The PCAP Touch-Monitor owns an impact-resistant and robust high-quality frameless touchscreen surface in Smartphone-Look for the usage in harsh environments which is made of tempered glass.

With its standardized ports and connections it can be tied to any suitable device.

To use the touchscreen function, the monitor is connected to your PC via USB port. The Installation and operation is as easy as winking an eye

Outstanding features of the WEWA-TV 21.5" PCAP Touchscreen-Monitors

▶ PCAP (Projective Capacitive Touchscreen-Technology), 10-point Touch (Win7/Win8/Win10)



Specifications 21.5" (54,61 cm) PCAP Touchscreen Monitor

▶ Article name	WEWA-TV 21.5" (54,61 cm) PCAP Touchscreen Monitor
▶ Article number / EAN	WT0215TMPCAP8 / 4260170311740
▶ Manufacturer	WEWA AG
▶ Screen size (inch) / (cm)	21.5 / 54,61
▶ Active display area (mm)	476.6 (H) x 268.1 (V)
▶ Aspect ratio	16:9
▶ Dimension (L x W x H - mm)	537.4 x 220 x 328.9
▶ Color Depth	16.7 M
▶ Physical Resolution	1920 x 1080@60Hz
▶ Pixel pitch (H x V)	0.248 x 0.248
▶ Response time (typ)	16 ms
▶ Brightness (cd/m ²)	250
▶ Contrast ratio (typ)	1000:1
▶ Viewing angle horizontal vertical (typ)	R/L: 85/85°, U/D: 80/80°
▶ OS	WinXP, Win7, Win8, Win10, Linux compatible
▶ Power Supply	Input voltage DC:12V ± 5%; extern: Power adaptor
▶ Power Consumption	23 W
▶ Operating temperature	0°C~45°C
▶ Storage temperature	-20°C~65°C
▶ HSF	31 KHz ~ 65 KHz
▶ VSF	56 KHz ~ 75 KHz
▶ Band width	178 MHz
▶ OSD	Contrast, Brightness, Horizontal vertical image size and position, Warm, Cool, User custom color temperature, the language selection, Recall function, Exit OSD
▶ Interface	RS232(C) USB 1.1 (optional)
▶ Touch activation force	80 g
▶ Input method	A finger or touch pen
▶ Reaction time Touch	<16 ms (Image <10 ms)
▶ Light transmission	92% (Glass thickness: 3mm)
▶ Minimum Touch Body	Ø 2.5 mm
▶ Continuous use (24/7)	•
▶ Mounting	100 mm VESA Mount
▶ Touch technology	PCAP (Projective Capacitive Touchscreen-Technology) 10-point Touch /Win7/Win8/Win10)
▶ I/O Ports	DVI, HDMI, VGA, USB-Touch port, Power

▶ Accessories

- | | |
|--|--|
| <input type="radio"/> WEWA-TV 21.5" PCAP Touchscreen Monitor | <input type="radio"/> 1x VGA-cable |
| <input type="radio"/> 1x 12V DC power supply unit | <input type="radio"/> 1x Driver CD (WinXP, Win7, Win8) |
| <input type="radio"/> 1x Monitor base | <input type="radio"/> 1x USB A-B cable |